

# PIスーパーAS

PI Super AS

ガラス

単焦点

非球面

1.90

## 仕様

屈折率	1.90
比重	3.89
アッペ数	30
設計	非球面

## 対応コート

- つるつる
- マルチ

## 製作範囲表

度数 (-)	球面	乱視 (-)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.50																	
11.00																	
.50																	
12.00																	
.50																	
13.00																	
.50																	
14.00																	
.50																	
15.00																	
.50																	
16.00																	
.50																	
17.00																	
.50																	
18.00																	
.50																	
19.00																	
.50																	
20.00																	

## カラー

ブラウン15%	○	※1
ブラウン25%	○	※1

## 原産国

日本

## 特殊加工

外径指定	×	
プリズム	○	※2
偏心	×	
カーブ指定	×	
UVカット	×	
厚み指定	×	
玉型カット	○	
スライス加工	×	
ツボクリ	○	

※1 つるつるは不可

※2 詳細はお問合せください。

## 仕様

屈折率	1.90
比重	3.89
アッペ数	30
設計	球面

## 対応コート

- つるつる
- マルチ

## 製作範囲表

度数 (-)	球面	乱視 (-)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.50																	
11.00																	
.50																	
12.00																	
.50																	
13.00																	
.50																	
14.00																	
.50																	
15.00																	
.50																	
16.00																	
.50																	
17.00																	
.50																	
18.00																	
.50																	
19.00																	
.50																	
20.00																	

## カラー

ブラウン15%	○	※1
ブラウン25%	○	※1

## 原産国

日本

## 特殊加工

外径指定	×	
プリズム	○	※2
偏心	○	※3
カーブ指定	×	
UVカット	×	
厚み指定	×	
玉型カット	○	
スライス加工	×	
ツボクリ	○	

※1 つるつるは不可

※2 詳細はお問合せください。

※3 詳細はお問合せください。

## 仕様

屈折率	1.80
比重	3.54
アッペ数	35
透過率	99.0 %
設計	非球面

## 対応コート

●マルチ

## 製作範囲表

度数 (-)	球面	乱視 (-)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.25																	
.50																	
.75																	
11.00																	
.25																	
.50																	
.75																	
12.00																	
.25																	
.50																	
.75																	
13.00																	
.25																	
.50																	
.75																	
14.00																	
.25																	
.50																	
.75																	
15.00																	
.50																	
16.00																	

## カラー

ブラウン15%	○	
ブラウン25%	○	

## 原産国

日本

## 特殊加工

外径指定	×	
プリズム	○	※1
偏心	×	
カーブ指定	×	
UVカット	標準	※2
厚み指定	×	
玉型カット	○	
スライス加工	×	
ツボクリ	○	

※1 詳細はお問合せください。

※2 UVB

## 仕様

屈折率	1.80
比重	3.54
アッペ数	35
透過率	99.0 %
設計	球面

## 対応コート

●マルチ

## 製作範囲表

度数 (-)	球 面	乱視 (-)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.25																	
.50																	
.75																	
11.00																	
.25																	
.50																	
.75																	
12.00																	
.25																	
.50																	
.75																	
13.00																	
.25																	
.50																	
.75																	
14.00																	
.25																	
.50																	
.75																	
15.00																	
.50																	
16.00																	
.50																	
17.00																	
.50																	
18.00																	
.50																	
19.00																	
.50																	
20.00																	

## カラー

ブラウン 15 %	○	
ブラウン 25 %	○	

## 原産国

日本

## 特殊加工

外径指定	×	
プリズム	○	※1
偏中心	○	※1
カーブ指定	×	
UVカット	×	
厚み指定	×	
玉型カット	○	
スライス加工	×	
ツボクリ	○	

※1 詳細はお問合せください。

※2 詳細はお問合せください。

## 仕様

屈折率	1.70
比重	3.20
アッペ数	35
透過率	99.0 %
設計	球面

## 対応コート

●マルチ

## 製作範囲表

在庫範囲 (マルチ)

度数 (-)	球面	乱視 (-)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
0.00																	
.25																	
.50																	
.75																	
1.00																	
.25																	
.50																	
.75																	
2.00																	
.25																	
.50																	
.75																	
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.25																	
.50																	
.75																	
11.00																	
.25																	
.50																	
.75																	
12.00																	
.25																	
.50																	
.75																	
13.00																	

## カラー

ブラウン15%	○	
ブラウン25%	○	

## 原産国

日本

## 特殊加工

外径指定	×	
プリズム	○	※1
偏心	○	※2
カーブ指定	×	
UVカット	標準	※3
厚み指定	×	
玉型カット	○	
スライス加工	×	
ツボクリ	○	

※1 詳細はお問合せください。

※2 詳細はお問合せください。

※3 UVB

## 仕様

屈折率	1.60
比重	2.63
アッペ数	41
透過率	99.0 %
設計	球面

## 対応コート

●マルチ

## 製作範囲表

■ 在庫範囲 (マルチ)

度数 (-)	球面	乱視 (-)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
0.00																	
.25																	
.50																	
.75																	
1.00																	
.25																	
.50																	
.75																	
2.00																	
.25																	
.50																	
.75																	
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	

度数 (+)	球面	乱視 (+)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
0.00																	
.25																	
.50																	
.75																	
1.00																	
.25																	
.50																	
.75																	
2.00																	
.25																	
.50																	
.75																	
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	

C(-)	混合乱視 (MIX)														
	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
S(+)															
0.25															
.50															
.75															
1.00															
.25															
.50															
.75															
2.00															
.25															
.50															
.75															
3.00															
.25															
.50															
.75															
4.00															

## カラー

ブラウン15%	○	
ブラウン25%	○	

原産国

日本

## 特殊加工

外径指定	○	※1
プリズム	○	※2
偏心	○	※3
カーブ指定	×	
UVカット	標準	※4
厚み指定	○	
玉型カット	○	
スライス加工	×	
ツボクリ	○	

※1 [縮小]

(+, MIX範囲) 基準径~最小55mm (5mm単位)

※2

(-) S+C=-6.00まで 3△まで可

(+) S+C=+2.00まで 3△まで可

(+) S+C=+6.00まで 1△まで可

※3

※2に準じた偏心量まで可

※4

UVB